

SiteWatch PRO3 Smart Security Camera

Up to 13 MP All-Weather Camera for Real-time Monitoring

SWPRO3VG-3-10x Camera Kit

Flexible, Reliable, Affordable

Sensera Systems' SiteWatch PRO3 day/night site monitoring solution combines thermal/lowlight and color cameras with IR illumination, video analytics and 4G LTE communications in one integrated system. This portable smart camera is perfect for 24/7 monitoring capable of realtime alert notifications (pushed to your email or mobile device). All video analytics are executed inside the camera, and only video relating to actual events is sent to the cloud for archival and















- Works with No Light on Site the thermal imager can detect people and vehicles with zero light, then uses the included IR illuminator to capture detail with the low-light camera.
- Long Range Detection the thermal camera provides longrange detection to cover more of the jobsite.
- **3-in-1 Camera System** thermal for detection, low-light for capturing detail in the lowest light conditions, and color for daytime and with sufficient ambient lighting. The intelligent system switches between camera sensors automatically to provide the best imagery based on light levels.

Access Your Camera 24/7

- 1080p video streaming and recording (configurable)
- Low-light detection with sensitive 4K camera
- Long-range motion detection covers large areas with fewer cameras
- Continuous video recording
- Schedule and automate capture of stills
- NDAA Compliant























SiteWatch PRO3 Security Camera

Technical Specifications

SWPRO3VG-3-10x Camera Kit



C/ (IVILITY)	
Color/Day	Camera

CAMERA

Image Sensor CMOS I3MP Sensor

Resolution 13 Megapixel on demand daytime,

8mp LiveView day, 1920 x 1080 (2mp)

zero-latency triggered day

Resolution (video stream) 640 x 480, 1280 x 720 (720p),

1920 x 1080 (1080p)

Video Compression H.264 or MJPEG Daytime Field of View (FoV) 74.9°(H) x 59.4°(V)

Resolution (recording) 640 x 480, 1280 x 720, 1920, 1080

High Dynamic Range (HDR) Day/night HDR for improved image

quality under uneven lighting conditions

Low-Light Black & White Camera

Image Sensor CMOS 4K Sensor

Resolution (still) 8mp on demand night illuminated

8mp LiveView night illuminated

2mp triggered night

Resolution (video stream)

(resolution triggered day/ night)

640 x 480, 1280 x 720,

1920 x 1080

H.264 or MJPEG Video Compression

Minimum Illumination $0.011 \, \text{Lix}$

Video Streaming MJPEG or H.264

Field of View (FoV) 120 diag 105°(H) x 59°(V)

High Dynamic Range (HDR) HDR for improved image quality under

day/night uneven lighting conditions

Thermal Detection Camera

Image Sensor LWIR, 8-14 µm Resolution (still) 160 x 120

Field of View (FoV) 45 (W) x 56 (diagonal)

Thermal Sensitivity <50mK

Video Analytics

Camera Input Thermal

Modes Motion detection with masking

Motion Detection Range

200' x 56° (Thermal)

Masking Multiple rectangular ignore areas

Edge Recording

Capacity 512GB (up to 137 days)

640 x 480, 10/60 second stills or Recording Resolution

continuous video

Scheduler (via SiteCloud) Up to 5 separate schedule segments

Prefetch Automatic uploads of clips on motion

events

ILLUMINATION

Illumination Type IR Power 36W Illumination Angle 609

NETWORK

Cellular 4G LTE (multiple carriers available)

WiFi 802.11 b/g/n

GPS Built-in GPS positioning

POWER

8-24VDC with Maximum Power Point Solar Power Input

Tracking (MPPT)

Solar Panel Included, 35W 31.02" x 13.78" x 1.18"

Auxiliary Power Input 18-24VDC

Battery Integrated rechargeable Lithium Iron

Phosphate (LiFePO4), 5 days power

Supply Power 110/220VAC input (a) < 0.74 Amps via

included AC/DC power adapter

Camera Power 18-24VDC @ < 2 Amps

PHYSICAL

Camera Dimensions 7.5"(W) x 6.25" (D) x 8.5" (H)

Camera Weight 7.5 lbs Solar Panel Weight 7.3 lbs

Mounting Hardware Pole/wall mount included

ENVIRONMENTAL

Operating Temperature -20°C (-4°F) to +50°C (122°F)

Enclosure Material Polycarbonate Encapsulation All-Weather IP65

SITECLOUD SERVICE RELATED FEATURES

Live streaming video

Video/image recording with web-based upload

Captured image/video archival and viewing

Edge storage: scheduled, configure, retrieve

Event notifications, trigger events via SMS, email, API

Motion detection: video analytics configuration, masking, arming schedules

ORDERING

SWPRO3VG-3-102 RT-SWPRO3VG 3-102-xxxx

(rental)

SWPRO3 Camera Kit (Solar or AC) Includes camera integrated battery pack, indoor AC adapter, solar panel and mounting brackets. Requires SiteCloud Service for operation.

SWPRO3VG-03-101 SWPRO3 Camera Kit (AC Power only)

Includes camera, outdoor AC power adapter, IR illumination and mounting brackets. Requires SiteCloud for

operation.

Available Carriers Verizon, AT&T, T-Mobile (United States)

Telus and Rogers (Canada).

Cloud Service Cellular plans start at IGB

Optional Accessories Roof Mount Kit, Tripod Kit, 20'

> Telescoping Pole, Portable Solar Trailer, Camera Transport Case, Outdoor AC

Adapter

SPECIFICATIONS SUBJECT TO CHANGE Images are for illustration purposes only

Manufactured in Golden, Colorado